

ROTARY / ROTARY W

AVVOLGITORE A BRACCIO ROTANTE PER FILM ESTENSIBILE
AUTOMATIC ROTATING ARM STRETCH WRAPPING MACHINES



CON TECNOLOGIA MLC
"MULTI-LEVEL CONTROL"
WITH MLC TECHNOLOGY
"MULTI-LEVEL CONTROL"



ROBOPAC

ROTARY / ROTARY W



- ✓ TOUCH SCREEN 7" A COLORI CON MULTILEVEL CONTROL
COLOUR TOUCH SCREEN 7" WITH MULTILEVEL CONTROL
- ✓ CONFIGURAZIONE A MURO
WALL CONFIGURATION
- ✓ PALLET INSTABILI E/O IRREGOLARI
UNSTABLE A/O IRREGULAR PALLETS
- ✓ IDEALE PER LOGISTICHE
IDEAL FOR LOGISTICS
- ✓ POSSIBILITA' DI FASCIARE PALLET FINO A 1400x1400 mm
POSSIBILITY TO WRAP PALLET TILL 1400x1400 mm
- ✓ BRACCIO ROTANTE REGOLABILE A SECONDA DELLE DIMENSIONI PALLET
ROTATING ARM ADJUSTABLE DEPENDING BY THE PALLET

CARATTERISTICHE TECNICHE / TECHNICAL FEATURES

MACCHINA / MACHINE

ROTARY / ROTARY W

Altezza utile albero / Usable mast height (mm)	2000 std./2400 opt./2750 opt.
Velocità rotazione braccio / Arm rotation speed (rpm)	7÷12
Velocità salita/discesa carrello regolabile da quadro / Carriage up/down speed adjustable from control panel (m/min)	2.5÷5.5
Produttività / Productivity (pallet/h)	20
Dimensioni minime pallet / Minimum pallet dimensions (LxW) (mm)	400x400
Dimensioni massime pallet / Maximum pallet dimensions (LxW) (mm)	1400x1400
Tipo carrello / Spool carriage type	FR/PDS/PVS
Bumper di emergenza a sensori ottici / Light Sensor Emergency Bumper	STD
Alimentazione / Power Supply (VAC)	230V±15% 1Ph+N 50/60 Hz
Arresto in fase / Phase stopping point	STD
Avvio progressivo / Soft start	STD
Fotocellula lettura altezza carico / Load height sensing by photocell	STD

