

Automatic Side-Seal Strapping Machine

The SQ-800Y with brushless DC Motor is a side-seal model which boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection.

■ **Wide Adaptability to Fully-Automated Packaging Line**

The machine fits any existing or proposed conveyor system, adapts to any conveyor height and requires no special equipment.

Several options are available to make it easy to integrate the SQ-800Y into a conveyor system. Larger arch sizes offer a wide range of applications, particularly for large and heavy packages.

■ **Strapping Speed**

Standard strapping cycle rate is 50 straps/min, even when tension is applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.

■ **Standard Operational Advantages**

Cycle Counter

■ **Optional Features**

Empty strap coil detection
Automatic strap tail ejection
Etc.



SQ-800Y



Standard Specifications (Arch Size 600mm wide x 850mm high)

Dimensions	Width	1500mm
	Height	1723mm
	Depth	610mm
	Weight	180kg
Package Size	Max.	W 580mm x H 820mm
	Min.	W 30mm x H 80mm
Joint / Strap		heat seal / polypropylene
Strap Width		5mm, 6mm, 9mm, 12mm, 15.5mm
Strap Tension		Max. 449N (45.8kgf)
Power Supply		100V, 120V, 220V, 230V, 240V - Single Phase - 50/60Hz - 0.74kVA

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2020 Strapack Corporation

DISTRIBUTED BY:



ISO 9001 and 14001 Certified

STRAPACK CORPORATION
8-16-6 Ginza, 104-0061 Chuo-ku, Tokyo, JAPAN
Phone: +81 3 6278 1806 Fax: +81 3 6278 1807
(URL) <http://www.strapack.com> (e-mail) info@strapack.com
STRAPACK INC.
33508, Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone: +1 510 475 6000 Fax: +1 510 475 6090
STRAPACK, N.V./S.A.
Uilenbaan 200, 2160 Wommelgem, BELGIUM
Phone: +32 3 355 15 20 Fax: +32 3 355 15 21