

High Speed Compact Automatic Strapping Machine

The SQ-800IR3 boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection, in an attractive and compact body.

■ Compact and Hand-Free

Space-efficient design with internal reel unit utilizing a standard size strap coil. The compact body is ideal for office, printing or mailing applications. And the integrated foot bar switch under the body provides handfree operation.

■ High Speed

Standard strapping cycle rate is 60 straps/min, even with tension applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.

■ Less Dusting and Less Moving Parts, with Self-Lubricating Design

The upgraded sealing head utilizing DC motors means less moving parts and less dusting from plastic strapping. It also reduces the maintenance cost. Strapack's signature self-lubricating design also reduces wear and tear, makes the maintenance easier, and increases operational life of the machine.

■ Standard Operational Advantages

- Foot Bar Switch
- Transport Handles
- Cycle Counter
- Big Caster Wheels
- Slide Table Switch
- Automatic Strap Tail Ejection

■ Other Features

- Easy Strap Loading
- Automatic Re-Feed
- Anti-Jam Function
- Loop Ejection



SQ-800IR3

Standard Specifications (Arch Size 650mm wide x 400mm high)

Dimensions	Width	1052mm (incl. transport handles)
	Height	1445mm
	Depth	609mm
	Weight	161kg
Table Height		936mm
Package Size	Max.	W 620mm x H 380mm
	Min.	W 80mm x H 30mm
Joint / Strap		heat seal / polypropylene
Strap Width		5mm, 6mm, 9mm, 12mm, 15.5mm
Strap Tension		Max. 449N (45.8kgf)
Power Supply		100V, 120V, 220V, 230V, 240V - Single Phase - 50/60Hz - 0.74kVA

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2019 Strapack

DISTRIBUTED BY:



ISO 9001 and 14001 Certified

STRAPACK N.V./S.A.
Uilenbaan 200, 2160 Wommelgem, BELGIUM
Phone: +32 3 355 15 20 Fax: +32 3 355 15 21
E-mail: europe@strapack.be